

# SPR-PVC-AS

IP 68  
-25°C ... +90°C ^ +100°C

EN / IEC 61386-23



Passende Verschraubungen  
Suitable connectors

		Seite   page	
	US-M	08. 2- 4	IP 65
	US-P	08. 5- 7	
	US2-M	08. 8	IP 65
	USDR-M	08.10	IP 65
	USZ-M	08.12	IP 65
	LI-M P	08.18	IP 40
	LIF-M P	08.19	IP 40
	USW-M	08.20-21	IP 65
	USW-P	08.22-23	

Metall-Schutzschlauch  
Stahl verzinkt  
PVC-Mantel, nicht flammverbreitend

Protective metal conduit  
galvanized steel  
PVC sheathing, non flame propagating

## KONSTRUKTION

wendelgewickelt  
S Profil  
PVC-Mantel

## STRUCTURE

strip-wound  
S profile  
PVC sheathing

## MATERIAL

**Schutzschlauch:** Kaltband DC 03/04 nach EN 10139, verzinkt, Fe/Zn 3  
**Andere Werkstoffe:** Aluminium, nichtrostender Stahl, Messing blank oder vernickelt  
**Mantel:** PVC  
Weitere Werkstoffe auf Anfrage

## MATERIAL

**Conduit:** cold strip DC 03/04 acc. to EN 10139, galvanized, Fe/Zn 3  
**Further materials:** aluminium, stainless steel, polished or nickel-plated brass  
**Sheathing:** PVC  
Please ask for further materials

## EIGENSCHAFTEN

- wetterfest
- wasserdicht
- weitgehend seewasser-, säure-, ölbeständig
- silikon- und cadmiumfrei
- sehr flexibel
- zugfest
- querdruckbelastbar
- DIN 49012, Bauform I geprüft nach DIN EN IEC 61386-23

## PROPERTIES

- weatherproof
- watertight
- widely resistant to seawater, acids, oils
- free of silicone and cadmium
- very flexible
- stretch-resistant
- compression-resistant
- DIN 49012, structural shape I, approved acc. to DIN EN IEC 61386-23

## ANWENDUNGSGEBIETE

- Maschinen- und Anlagenbau
- Fahrzeugbau
- Schiffsbau
- Automation
- Elektroanlagen

## APPLICATION

- machine and plant constructions
- automotive
- shipbuilding
- automation
- electrical installations



FLEXA No.

FLEXA No

AD  
OD



schwarz black

grau grey

ø

mm

stat

dyn

kg/m

m



2010.112.007	2010.111.007	10	7,0 x 10,0	25	65	0,079	50
2010.112.010	2010.111.010	14	10,0 x 14,0	37	95	0,130	50
2010.112.013	2010.111.013	17	13,0 x 17,0	45	115	0,170	50
2010.112.015	2010.111.015	19	15,0 x 19,0	50	120	0,190	50
2010.112.017	2010.111.017	21	17,0 x 21,0	55	140	0,240	50
2010.112.022	2010.111.022	27	22,0 x 27,0	60	150	0,360	50
2010.112.029	2010.111.029	36	29,0 x 36,0	90	225	0,600	25
2010.112.038	2010.111.038	45	38,0 x 45,0	120	300	0,740	25
2010.112.049	2010.111.049	56	49,0 x 56,0	130	325	0,900	25

Verkaufsverpackung 10 m

10 m sales pack

2011.112.007	2011.111.007	10	7,0 x 10,0	25	65	0,079	10
2011.112.010	2011.111.010	14	10,0 x 14,0	37	95	0,130	10
2011.112.013	2011.111.013	17	13,0 x 17,0	45	115	0,170	10
2011.112.015	2011.111.015	19	15,0 x 19,0	50	120	0,190	10
2011.112.017	2011.111.017	21	17,0 x 21,0	55	140	0,240	10
2011.112.022	2011.111.022	27	22,0 x 27,0	60	150	0,360	10
2011.112.029	2011.111.029	36	29,0 x 36,0	90	225	0,600	10
2011.112.038	2011.111.038	45	38,0 x 45,0	120	300	0,740	10**
2011.112.049	2011.111.049	56	49,0 x 56,0	130	325	0,900	10**

\*\* in Ringen \*\* in rings