



IP 68
 -25°C ... +80°C ^ +100°C



SPR-VA-PVC

Metall-Schutzschlauch
 Edelstahl
 PVC-Mantel, nicht flammverbreitend
 nach DIN EN IEC 61386-23

Protective metal conduit
 stainless steel
 PVC sheathing, non flame propagating
 acc. to DIN EN IEC 61386-23

KONSTRUKTION

wendelgewickelt
 S Profil, PVC-Mantel

STRUCTURE

strip-wound
 S profile, PVC sheathing

MATERIAL

Schutzschlauch: Edelstahl
 Ummantelung: PVC
 Andere Werkstoffe auf Anfrage

MATERIAL

Conduit: stainless steel
 Sheathing: PVC
 Further materials on request

EIGENSCHAFTEN

- wetterfest
- wasserdicht
- weitgehend seewasser-, säure- und ölbeständig
- silikon- und cadmiumfrei
- sehr flexibel
- zugfest
- querdruckbelastbar

PROPERTIES

- weatherproof
- watertight
- widely resistant to seawater, acids and oils
- free of silicone and cadmium
- very flexible
- stretch-resistant
- compression-resistant

ANWENDUNGSGEBIETE

- Maschinen- und Anlagenbau
- Fahrzeugbau
- Schiffsbau
- Automation
- Elektroanlagen
- Optoelektronik
- Lichtwellenleiter-Technik
- Technische Endoskopie
- Sensortechnik

APPLICATION

- machine and plant constructions
- automotive
- shipbuilding
- automation
- electrical installations
- opto-electronics
- beam wave guide technology
- technical endoscopy
- sensor technology



IBISEP
 ELECTRONIC PRODUCTS GROUP
 1-800-350-7937 | www.ibisep.com | info@ibisep.com

FLEXA No.



mm



stat dyn



m



kg/m



m

schwarz black



FLEXA No.	mm	stat	dyn	m	kg/m	m
1 2010 182 003	3,0 x 6,0	15	37	500	0,040	50
1 2010 182 004	4,0 x 7,0	17	45	500	0,050	50
1 2010 182 005	5,0 x 8,0	20	50	500	0,060	50
1 2010 182 006	6,0 x 9,0	25	60	500	0,080	50
1 2010 182 008	8,0 x 11,0	35	90	500	0,090	50
1 2010 182 009	9,0 x 12,0	38	100	500	0,105	50

Weitere Abmessungen und Farben auf Anfrage Further dimensions and colours on request