



### Flachdichtring

#### Material Perbunan

#### Eigenschaften

- beständig gegen Öl
- Abdichtung gegen Wasser und Staub

### Flat-sealing

#### Material perbunan

#### Properties

- resistant against oil
- protection against water and dust



ELECTRO-PRODUCTS CORP.

1-800-350-7937 | www.ibisep.com | info@ibisep.com

FLEXA No.								
Perbunan				ød mm	øD mm	S mm	kg/100	St. Pcs.
<b>FR-M</b>	<b>Metr.</b> EN 60423							
0333.000.010	<b>M 10</b>			10,0	17,0	1,5	0,032	50
0333.000.012	<b>M 12</b>			12,0	20,0	1,5	0,046	50
0333.000.016	<b>M 16</b>			16,0	23,0	2,0	0,064	50
0333.000.020	<b>M 20</b>			20,0	29,0	2,0	0,104	50
0333.000.025	<b>M 25</b>			25,0	37,0	2,0	0,200	50
0333.000.032	<b>M 32</b>			32,0	44,0	2,0	0,240	25
0333.000.040	<b>M 40</b>			40,0	52,0	2,0	0,200	25
0333.000.050	<b>M 50</b>			50,0	64,0	2,5	0,600	25
0331.000.018	<b>M 63</b>			60,5	66,0	3,0	0,460	10
<b>FR-P</b>	<b>PG</b> DIN 40430							
0331.000.007	<b>7</b>			11,5	16,0	2,0	0,034	50
0331.000.009	<b>9</b>			14,0	20,0	2,0	0,050	50
0331.000.011	<b>11</b>			18,5	22,5	2,0	0,040	50
0331.000.013	<b>13,5</b>			19,0	25,0	2,0	0,064	50
0331.000.016	<b>16</b>			21,0	27,0	2,0	0,066	50
0331.000.021	<b>21</b>			27,0	34,0	2,5	0,144	25
0331.000.029	<b>29</b>			35,0	43,0	2,5	0,240	25
0331.000.036	<b>36</b>			45,0	54,0	2,5	0,320	25
0331.000.048	<b>48</b>			57,5	68,0	3,0	0,600	10
<b>FR-N/C</b>	<b>NPT</b> ANSI/ASME B1.20.1	<b>CTG</b> JIS B 0204	<b>Whitworth</b> DIN ISO 228-1					
0331.000.002	<b>1/4"</b>		<b>1/4"</b>	14,0	17,0	1,5	0,026	50
0331.000.011	<b>3/8"</b>		<b>3/8"</b>	18,5	22,5	2,0	0,040	50
0331.000.016	<b>1/2"</b>	<b>G16</b>	<b>1/2"</b>	21,0	27,0	2,0	0,066	50
0331.000.021	<b>3/4"</b>	<b>G22</b>	<b>3/4"</b>	27,0	34,0	2,5	0,144	25
0331.000.045	<b>1"</b>	<b>G28</b>	<b>1"</b>	34,0	43,0	2,0	0,164	25
0331.000.008	<b>1 1/4"</b>	<b>G36</b>	<b>1 1/4"</b>	42,5	51,0	3,0	0,280	25
0331.000.014	<b>1 1/2"</b>		<b>1 1/2"</b>	48,5	55,0	3,0	0,200	25
0331.000.018	<b>2"</b>	<b>G54</b>	<b>2"</b>	60,5	66,0	3,0	0,320	10