

Gegenmutter

Material Messing, vernickelt

Verwendung

Gegenmutter speziell für Metallgewinde

Counternut

Material nickel-plated brass



Application

Counternut especially for metal threads



ELECTRO-PRODUCTS CORP.

1-800-350-7937 | www.ibisep.com | info@ibisep.com

| FLEXA No. |  |  |  |  | |
|-----------------|---|---|---|---|-------------|
| | | SW mm | S mm | kg/100 | St. Pcs. |
| GM-M | | | | | |
| | Metr. EN 60423 | | | | |
| 0531.000.010 | M 10 x 1,0 | 14 | 2,5 | 0,110 | 100 |
| 0531.000.012 | M 12 x 1,5 | 15 | 2,8 | 0,220 | 100 |
| 0531.000.016 | M 16 x 1,5 | 19 | 2,8 | 0,300 | 100 |
| 0531.000.020 | M 20 x 1,5 | 24 | 3,0 | 0,510 | 100 |
| 0531.000.025 | M 25 x 1,5 | 30 | 3,5 | 0,910 | 100 |
| 0531.000.032 | M 32 x 1,5 | 36 | 4,0 | 1,080 | 100 |
| 0531.000.040 | M 40 x 1,5 | 46 | 5,0 | 2,420 | 50 |
| 0531.000.050 | M 50 x 1,5 | 60 | 5,0 | 4,820 | 50 |
| 0531.000.063 | M 63 x 1,5 | 70 | 6,0 | 5,560 | 50 |
| GM-P | | | | | |
| | PG DIN 40430 | | | | |
| 0530.000.007 | 7 | 15 | 2,8 | 0,190 | 100 |
| 0530.000.009 | 9 | 18 | 2,8 | 0,270 | 100 |
| 0530.000.011 | 11 | 21 | 3,0 | 0,310 | 100 |
| 0530.000.013 | 13,5 | 23 | 3,0 | 0,350 | 100 |
| 0530.000.016 | 16 | 26 | 3,0 | 0,500 | 100 |
| 0530.000.021 | 21 | 32 | 3,5 | 0,770 | 100 |
| 0530.000.029 | 29 | 41 | 4,0 | 1,290 | 100 |
| 0530.000.036 | 36 | 51 | 5,0 | 2,180 | 50 |
| 0530.000.048 | 48 | 64 | 5,5 | 3,440 | 25 |
| GM-N /-C | | | | | |
| | NPT ANSI/ASME B1.20.1 | | | | |
| 0531.000.002 | 3/8" | 20 | 3,0 | 0,360 | 100 |
| 0531.000.003 | 1/2" | 24 | 3,0 | 0,430 | 100 |
| 0531.000.004 | 3/4" | 30 | 3,5 | 0,740 | 100 |
| 0531.000.005 | 1" | 38 | 4,0 | 1,540 | 100 |
| 0531.000.006 | 1 1/4" | 46 | 5,0 | 1,950 | 100 |
| 0531.000.007 | 1 1/2" | 51 | 5,0 | 2,060 | 100 |
| 0531.000.008 | 2" | 64 | 5,5 | 3,450 | 50 |



- Portrait
- ROHRflex Wellenschlauch
- FLEXAquick Anschlusstechnik
- Metall Schläuche
- Metall Schläuche - dicht -
- Kunststoff Schläuche
- Spezial Schläuche
- Anschluss-technik
- Zubehör