

Metallverschraubung
gerade
Außengewinde

Konstruktion
Rundes Verschraubungsgehäuse
mit Sechskantschlüsselfläche,
feststehendes Außengewinde metrisch
nach EN 60423 oder PG nach DIN 40430

Material
Gehäuse Messing vernickelt
Abdeckhülse Messing vernickelt

Eigenschaften

- integrierte Schlauchausdreh Sperre
- Abdeckung der Schlauchenden
- vibrations- und zugfest

Montage
Abdeckhülse auf das Schlauchende
stecken und danach das
Verschraubungsgehäuse eindrehen

Metal connector
straight
outer thread



Structure
Round connector body
hexagonal wrench surface
fixed outer thread metric acc. to
EN 60423 or PG acc. to DIN 40430

Material
Connector body nickel-plated brass
Cover sleeve nickel-plated brass

Properties

- integrated conduit screw out
- covering of the conduit ends
- vibrationproof and tensionproof

Assembly
Push the cover sleeve on the end of the
conduit and screw the connector in
the conduit



A Verschraubungsgehäuse
connector body
B Abdeckhülse
cover sleeve



Portrait

ROHrflex
Wellenschlauch

FLEXAquick
Anschluss-
technik

Metall
Schläuche

Metall
Schläuche
- dicht -

Kunststoff
Schläuche

Spezial
Schläuche

Anschluss-
technik

| | | | | | | | | | | |
|----------|--|-----------|--|--|--|--|--|--|-----------|--|
| AD OD | | FLEXA No. | | | | | | | FLEXA No. | |
|----------|--|-----------|--|--|--|--|--|--|-----------|--|

| LIF-M | | | | | | | | | | Kleine VPE Small packing unit | |
|-------|-------------------|--------------|----------|----------|---------|---------|----------|--------|-------------|----------------------------------|-------------|
| ø | Metr. EN 60423 | [IP 40] | øl mm | øB mm | C mm | D mm | SW mm | kg/100 | St. Pcs. | | St. Pcs. |
| 10 | M 12 x 1,5 | 5801.310.012 | 5,9 | 16,0 | 10,0 | 26,0 | 15 | 1,550 | 50 | 5801.810.012 | 10 |
| 14 | M 16 x 1,5 | 5801.314.016 | 8,9 | 21,0 | 10,0 | 27,0 | 19 | 2,400 | 50 | 5801.814.016 | 10 |
| 17 | M 16 x 1,5 | 5801.317.016 | 11,0 | 25,0 | 10,0 | 27,0 | 23 | 3,000 | 50 | 5801.817.016 | 10 |
| 17 | M 20 x 1,5 | 5801.317.020 | 12,0 | 25,0 | 10,0 | 27,0 | 23 | 2,900 | 50 | 5801.817.020 | 10 |
| 21 | M 20 x 1,5 | 5801.321.020 | 15,0 | 29,0 | 10,0 | 27,0 | 27 | 3,800 | 50 | 5801.821.020 | 10 |
| 27 | M 25 x 1,5 | 5801.327.025 | 20,0 | 37,0 | 11,0 | 30,5 | 34 | 6,300 | 25 | 5801.827.025 | 10 |
| 36 | M 32 x 1,5 | 5801.336.032 | 27,5 | 45,6 | 13,0 | 33,0 | 43 | 9,160 | 25 | 5801.836.032 | 2 |
| 45 | M 40 x 1,5 | 5801.345.040 | 35,0 | 59,0 | 13,0 | 33,0 | 54 | 13,300 | 25 | 5801.845.040 | 2 |
| 56 | M 50 x 1,5 | 5801.356.050 | 45,0 | 69,0 | 14,0 | 34,0 | 66 | 18,500 | 10 | 5801.856.050 | 2 |

| LIF-P | | | | | | | | | | Kleine VPE Small packing unit | |
|-------|-----------------|--------------|----------|----------|---------|---------|----------|--------|-------------|----------------------------------|-------------|
| ø | PG DIN 40430 | [IP 40] | øl mm | øB mm | C mm | D mm | SW mm | kg/100 | St. Pcs. | | St. Pcs. |
| 10 | 7 | 5801.010.007 | 5,9 | 16,0 | 10,0 | 26,0 | 15 | 1,600 | 50 | 5801.410.007 | 10 |
| 14 | 9 | 5801.014.009 | 8,9 | 21,0 | 10,0 | 27,0 | 19 | 2,400 | 50 | 5801.414.009 | 10 |
| 17 | 11 | 5801.017.011 | 12,0 | 25,0 | 10,0 | 27,0 | 23 | 2,900 | 50 | 5801.417.011 | 10 |
| 19 | 13,5 | 5801.019.013 | 14,0 | 27,0 | 10,0 | 27,0 | 25 | 3,200 | 50 | 5801.419.013 | 10 |
| 21 | 16 | 5801.021.016 | 15,9 | 29,0 | 10,0 | 27,0 | 27 | 3,900 | 50 | 5801.421.016 | 10 |
| 27 | 21 | 5801.027.021 | 20,4 | 37,0 | 11,0 | 30,6 | 34 | 6,200 | 25 | 5801.427.021 | 10 |
| 36 | 29 | 5801.036.029 | 27,5 | 45,6 | 13,0 | 33,0 | 43 | 8,800 | 25 | 5801.436.029 | 2 |
| 45 | 36 | 5801.045.036 | 36,6 | 59,0 | 13,0 | 33,0 | 54 | 11,750 | 25 | 5801.445.036 | 2 |
| 56 | 48 | 5801.056.048 | 47,5 | 69,0 | 13,5 | 33,5 | 66 | 16,400 | 10 | 5801.456.048 | 2 |

