

OR

-20°C ... +120°C



**O-Ring**

**Material** Perbunan

**Eigenschaften**

- beständig gegen Öl
- Abdichtung gegen Wasser und Staub

**O-ring**

**Material** perbunan

**Properties**

- resistant against oil
- protection against water and dust



**ELECTRO-PRODUCTS CORP.**

1-800-350-7937 | www.ibisep.com | info@ibisep.com

FLEXA No.				ød mm	S mm	kg/100	St. Pcs.
<b>OR-M</b>		<b>Metr. EN 60423</b>					
0330.001.010	<b>M 10</b>			8,0	1,5	0,012	50
0330.001.012	<b>M 12</b>			10,0	1,5	0,012	50
0330.001.016	<b>M 16</b>			14,0	2,0	0,026	50
0330.001.020	<b>M 20</b>			18,0	2,0	0,028	50
0330.001.025	<b>M 25</b>			23,0	2,0	0,036	50
0330.001.032	<b>M 32</b>			30,0	2,0	0,040	25
0330.001.040	<b>M 40</b>			38,0	2,5	0,092	25
0330.001.050	<b>M 50</b>			48,0	2,5	0,108	25
0330.001.063	<b>M 63</b>			61,0	3,0	0,200	10
<b>OR-P</b>		<b>PG DIN 40430</b>					
0330.000.007	<b>7</b>			10,0	1,5	0,014	50
0330.000.009	<b>9</b>			12,5	1,8	0,018	50
0330.000.011	<b>11</b>			16,0	2,0	0,028	50
0330.000.013	<b>13,5</b>			18,0	2,0	0,056	50
0330.000.016	<b>16</b>			20,0	2,0	0,032	50
0330.000.021	<b>21</b>			26,0	2,0	0,044	25
0330.000.029	<b>29</b>			34,0	2,0	0,052	25
0330.000.036	<b>36</b>			44,0	2,5	0,096	25
0330.000.048	<b>48</b>			53,0	2,5	0,100	10

Portrait

ROHRflex  
Conduits

FLEXAquick  
Connectors

Metal  
Conduits

Metal  
Conduits  
Liquid tight

Plastic  
Conduits

Special  
Conduits

Connectors

Accessories