

# RQBK90DR

IP 68 / IP 69K

-40 °C ... +115 °C




**Kunststoff-Schnellverschraubung**  
**Bogen 90°**  
**drehbares Messingaußengewinde**  
**hochdichtend**  
 inkl. O-Ring [OR] und Flachdichtring [FRH]

**Plastic connector, quick-type**  
**bend 90°**  
**tunable outer thread made of**  
**nickel-plated brass, high sealing rate**  
 incl. OR O-ring and FRH flat-sealing

- beständig gegen Öl und Benzin
- weitgehend säure- und lösungsmittelbeständig
- silikon-, cadmium- und halogenfrei
- hohe mechanische Belastbarkeit
- Schlagfestigkeit
- hohes Drehmoment des Gewindeanschlusses
- Positionierung auch nach der Montage möglich

- resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- fit for high mechanical stress
- impact-resistant
- high torque of thread connection
- swiveling also after installation



EN / IEC 61386-23

UL 1696  
 AD/OD 21,2 - 54,5

DIN 5510-2 (S1)

NFF 16-101/102  
 (B / F2)

EN 45545-2 (HL 2)



**ELECTRO-PRODUCTS CORP.**  
 1-800-350-7937 | www.ibisep.com | info@ibisep.com



FLEXA No.	AD OD										
schwarz black	ø		øl mm	øB mm	C mm	E mm	F mm	SW mm	kg/100	St. Pcs.	
<b>RQBK90DR-M</b>		<b>Metr.</b> EN 60423								<b>[IP 68 / 69K]</b>	
5121.021.220	<b>21,2</b>	<b>M 20 x 1,5</b>	13,0	29,5	12,0	72,0	62,0	27	6,200	50	
5121.028.225	<b>28,5</b>	<b>M 25 x 1,5</b>	17,0	37,0	13,0	90,0	80,0	34	11,160	25	
5121.034.232	<b>34,5</b>	<b>M 32 x 1,5</b>	24,5	44,0	14,0	100,0	91,0	43	16,500	10	
5121.042.240	<b>42,5</b>	<b>M 40 x 1,5</b>	31,5	52,0	17,0	111,0	103,0	52	28,400	10	
<b>RQBK90DR-P</b>		<b>PG</b> DIN 40430								<b>[IP 68 / 69K]</b>	
5521.021.216	<b>21,2</b>	<b>16</b>	13,0	29,5	13,0	72,0	62,0	27	6,220	50	
5521.028.221	<b>28,5</b>	<b>21</b>	17,0	37,0	14,0	85,0	79,0	34	11,000	25	
5521.034.229	<b>34,5</b>	<b>29</b>	24,5	44,0	14,0	100,0	91,0	43	16,000	10	
5521.042.236	<b>42,5</b>	<b>36</b>	31,5	52,0	17,0	110,0	103,0	52	32,900	10	
<b>RQBK90DR-N</b>		<b>NPT</b> ANSI/ASME B1.20.1								<b>[IP 68 / 69K]</b>	
5020.019.206*	<b>21,2</b>	<b>1/2"</b>	13,0	29,5	14,0	73,0	65,0	27	7,100	50	
5020.019.214*	<b>28,5</b>	<b>3/4"</b>	17,0	37,0	14,0	90,0	81,5	34	12,000	25	
5020.019.216*	<b>34,5</b>	<b>1"</b>	24,5	44,0	18,0	100,0	95,0	43	17,400	10	
5020.019.217*	<b>42,5</b>	<b>1 1/4"</b>	31,5	52,0	18,0	111,0	105,0	52	30,500	10	

\* Lieferzeit auf Anfrage  
 \* Delivery time on request



Portrait

ROHRflex  
 Conduits

FLEXAquick  
 Connectors